

# DA-L1A2500.1F

## EXTREME A2.5K FULL RANGE

### FULL RANGE AMPLIFIER CLASS D

MAX POWER: 2500 WATTS  
 FREQUENCY RESPONSE: 20Hz-20KHz  
 SENSITIVITY: 0.2-6V

### FEATURES

- 2 Layers PCB
- LED indicator
- Stable and reliable circuit design
- Surface mount component technology
- Small size footprint for easy installation
- Audio precision quality control verification
- Direct insert power and speaker terminals
- Short circuit, thermal and voltage protection

### GENERAL SPECIFICATIONS

- Max Power: 2500 W
- Signal to Noise Ratio:  $\geq 80$ DB
- Frequency Response: 20Hz-20KHz
- Crossover High Pass (HPF): 10Hz-3.2KHz
- Crossover Low Pass (LPF): 50Hz-20Hz
- Bass Boost: 0-12 DB
- Impedance of Entry: 1 Ohm
- High speed mosfet power supply
- Micro size architecture with SMD



### RMS POWER

- (4 Ohms: 640W RMS x 1 CH)
- (2 Ohms: 1100W RMS x 1 CH)
- (1 Ohm: 1500W RMS x 1 CH)

### DIMENSIONS

320 mm x 112 mm x 46 mm

