

DA-H1M10+

ULTIMATE M10+

10" MIDRANGE SPEAKER

GENERAL SPECIFICATIONS

Nominal Power Handling	600W
Transient Power 10ms	300W
Sensitivity	99dB
Frequency Response	74-5.5kHz
Cone Material	PAPER
Net Weight	7.9Kg

MAX POWER:	600
RMS POWER:	300W
FREQUENCY RESPONSE:	74-5500Hz
SENSITIVITY:	99dB
VOICE COIL:	75.5 mm

Electrical Data

Nominal Impedance	8 Ohm
DC Resistance	5.2 Ohm

Voice Coil And Magnet Parameters

Voice Coil Diameters	75.5mm
Voice Coil Height	11mm
Gap Height	8mm
Max. Linear Excursion	3.15mm
Voice Coil Wire	GPI (inside-outside)
Number of Layer	2
Magnet System Type	Ferrite
BL Product	21.7 N.A



Thiele-Small Parameters

Cms	0.065
Qms	9.35
Qes	0.24
Qts	0.23
MMS	46.8
VAS	18.22
FS	74 Hz
Sd	363.05 cm ²

MOUNTING INFO

Overall Diameter:	262mm	Mounting Depth:	112mm
Front Mount Baffle Cutout:	234mm	Overall Depth:	129mm

SPL vs FREQ

